



OpenVox VS-GWM801-O

VS-GWM801-O module Supports Open Vox VS-GW1202/1600/2120 series Analog gateways to allow Analog telephone connection in the VoIP devices. Each module features 8 FXO analog telephone channels.



Features

- | | |
|---|---|
| <ul style="list-style-type: none">◆ 8 ports on 1 module◆ Echo cancellation and Static jitter buffer◆ Ring cadence and frequency setting◆ MWI (Message waiting indicator)◆ DHCP、DNS/DDNS、NAT networking◆ Update firmware online◆ Configuration file backup and upload◆ Restore the factory settings | <ul style="list-style-type: none">◆ T.38 fax relay and T.30 fax transparent, continually fax multiple pages◆ Diverse SIP protocols◆ Diverse extensible applications, such as IVR, DISA◆ Independent system for each module◆ Available for OEM |
|---|---|

Technical Specification	
<ul style="list-style-type: none"> ◆ Operation temperature range: 0~50°C ◆ Max Power Consumption: 12W ◆ Weight: 162g 	<ul style="list-style-type: none"> ◆ Storage temperature range: -40~125°C ◆ Operation humidity range: 10%~90% ◆ Dimension:13cm × 2.1cm × 20cm

Open Vox VS-GWM801-O			
Module Type	GSM	WCDMA	LTE
Band	850/900/1800/1900MHz@GSM	900/2100MHz@UMTS 900/1800MHz@GSM	LTE FDD: B1/B3/B5/B8 LTE TDD: B38/B39/B40/B41 WCDMA: B1/B8 TD-SCDMA: B34/B39 CDMA: BC0 GSM: 900/1800MHz

Office Address	Contact Us Via Mobile	Contact Us Via Mail
----- Asfera Technologies Private Limited , Saroj Tower, Office No:- 15 First Floor, 59/1, above Bank of Baroda, Kalkaji Extension, New Delhi, 110019.	----- +91-9066677770 +91-1146579777	----- info@asfera.in info@gsmgateway.in sales@asfera.in