



**OpenVox VS-GWM801-OS**

VS-GWM801-O/S module Supports Open Vox VS-GW1202/1600/2120 series Analog gateways to allow Analog telephone connection in the VoIP devices. Each module features 4FXO and 4 FXS analog telephone channels.



**Features**

- |  |   |
|--|---|
| <ul style="list-style-type: none"> <li>◆ 8 ports on 1 module</li> <li>◆ Echo cancellation and Static jitter buffer</li> <li>◆ Ring cadence and frequency setting</li> <li>◆ MWI (Message waiting indicator)</li> <li>◆ DHCP、DNS/DDNS、NAT networking</li> <li>◆ Update firmware online</li> <li>◆ Configuration file backup and upload</li> <li>◆ Restore the factory settings</li> </ul> | <ul style="list-style-type: none"> <li>◆ T.38 fax relay and T.30 fax transparent, continually fax multiple pages</li> <li>◆ Diverse SIP protocols</li> <li>◆ Diverse extensible applications, such as IVR, DISA</li> <li>◆ Independent system for each module</li> <li>◆ Available for OEM</li> </ul> |
|--|---|

<b>Technical Specification</b>	
<ul style="list-style-type: none"> <li>◆ Operation temperature range: 0~50°C</li> <li>◆ Max Power Consumption: 12W</li> <li>◆ Weight: 155g</li> </ul>	<ul style="list-style-type: none"> <li>◆ Storage temperature range: -40~125°C</li> <li>◆ Operation humidity range: 10%~90%</li> <li>◆ Dimension:13cm × 2.1cm × 20cm</li> </ul>

<b>Open Vox VS-GWM801-OS</b>			
Module Type	GSM	WCDMA	LTE
Band	850/900/1800/1900MHz@GSM	900/2100MHz@UMTS 900/1800MHz@GSM	LTE FDD: B1/B3/B5/B8 LTE TDD: B38/B39/B40/B41 WCDMA: B1/B8 TD-SCDMA: B34/B39 CDMA: BC0 GSM: 900/1800MHz

<b>Office Address</b>	<b>Contact Us Via Mobile</b>	<b>Contact Us Via Mail</b>
----- Asfera Technologies Private Limited , Saroj Tower, Office No:- 15 First Floor, 59/1, above Bank of Baroda, Kalkaji Extension, New Delhi, 110019.	----- <b>+91-9066677770</b>  <b>+91-1146579777</b>	----- <a href="mailto:info@asfera.in">info@asfera.in</a>  <a href="mailto:info@gsmgateway.in">info@gsmgateway.in</a>  <a href="mailto:sales@asfera.in">sales@asfera.in</a>