



**OpenVox VS-GW1600 V2 GSM Wireless Gateway**

VS-GW1600 V2 Wireless Gateway, an updated product of the VS-GW1600 Series, is now the leading open source Asterisk-based VoIP Gateway easy for SMBs and SOHOs. The VS-GW1600 V2 Wireless Gateway with the Modular Design can provide up to 5 plug-in GSM/WCDMA/LTE gateway modules which could easily from 4 to 20 GSM/WCDMA/LTE channels, developed for interconnecting a wide pick of codecs, including 2G/3G/4G networks to the G.711A, G.711U, G.729, G.722, G.723, G.726 & GSM, to easily reduce telecommunication expenses and maximize cost budget. With the different designs for VS-GW1600 V2 Wireless Gateway



**Features**

- |  |  |
|--|--|
| <ul style="list-style-type: none"> <li>◆ Simple and convenient configuration via Web GUI</li> <li>◆ Support http / https / SSH</li> <li>◆ Basic security strategy (white/black list, security rules)</li> <li>◆ Optional GSM Voice Codec</li> <li>◆ SIP(RFC3261) compliance</li> </ul> | <ul style="list-style-type: none"> <li>◆ Codecs support: G.711A, G.711U, G.729, G.723.1, G.722, G.726, GSM</li> <li>◆ Support diverse SIP, IAX2 protocols</li> <li>◆ Support diverse SIP, IAX2 protocols</li> <li>◆ Multiple SIP/IAX2 Registration models: None, server, client</li> <li>◆ DTMF Signaling support: RFC2833, Inband, SIPINFO</li> </ul> |
|--|--|

OpenVox VS-GWM401W Gateway Frequency Range			
Module Type	GSM	WCDMA	LTE
Band	850/900/1800/1900MHz@GSM	900/2100MHz@UMTS 900/1800MHz@GSM	LTE FDD: B1/B3/B5/B8 LTE TDD: B38/B38/B40/B41 WCDMA: B1/B8 TD-SCDMA: B34/B39 CDMA: BC0 GSM: 900/1800MHz

<b>Office Address</b> ----- Asfera Technologies Private Limited , Saroj Tower,Office No:- 15 First Floor, 59/1, above Bank of Baroda, Kalkaji Extension, New Delhi, 110019.	<b>Contact Us Via Mobile</b> ----- +91-9066677770 +91-1146579777	<b>Contact Us Via Mail</b> ----- <a href="mailto:info@asfera.in">info@asfera.in</a> <a href="mailto:sales@asfera.in">sales@asfera.in</a>
--	---	---